

Power

Tri Power X33 Mod HP

High Performance
Modular 3-phase UPS-System 10 to 60 kVA



- Modular and scalable from 10 to 60kVA
- High Output Power Factor 0.9
- Easy to install - easy to handle - easy to maintain
easy to expand
- Customized configuration with 3.4, 5.0
and 6.7 kVA Power Modules
- High Performance on a small foot print: i.e. 15 kVA system with N+1 Redundancy
- totally modular - with 5 minutes back up time in one single cabinet
- Cost effective N+x redundancy; even phase by phase
- Modular Battery System
- Advanced Battery Management
- Double Input (Model HP40, 45 and 45kVA)

The unique Tri Power Mod HP Systems from Alpha Technologies are the only UPSs which are combining all relevant aspects to achieve an efficient, economical and long life UPS system with all advantages of a modular, scalable and redundant UPS architecture. The true modularity of the Tri Power X33 Mod HP allows an individual and progressive adaption to the current IT environment while considering future load changes.

Each power module – available as 3.4, 5.0 and 6.7kVA modules – is redundant to the other and allows an individual, customized configuration – almost 50 different configurations are possible with only 3 power cabinets. Their maximum weight of 9kg allows an easy installation and replacement which can be performed by a single person. Tri Power X33 Mod HP are easy to install, easy to handle, easy to maintain and easy to expand at any time for future requirements. Tri Power X33 Mod HP technologically balances the dynamic changes within the IT equipment – i.e. due to product life cycles, technology changes and consolidations – and the capabilities of the power supply. This makes Tri Power X33 Mod HP the first choice for all IT applications.



Tri Power X33 Mod HP 10 to 60 kVA

Technical Specifications							
Model	X33 Mod HP 10	X33 Mod HP 15	X33 Mod HP 20	X33 Mod HP 30	X33 Mod HP 40	X33 Mod HP 45	X33 Mod HP 60
Nominal Power (kVA)	10	15	20	30	40	45	60
Architecture of the UPS	Modular, scalable and redundant in one single cabinet				Modular, scalable and redundant		
INPUT							
Nominal Voltage	230V 1-phase / 400V 3-phase +N			400V 3 phase +N			
Frequency	50 Hz / 60 Hz +/- 2% autosensing						
Compatibility with gensets	Configurable for synchr. between the input and output frequencies, even for the highest frequency ranges, +/- 14%						
Power Factor at full load	> 0,99						
THD of input current	≤ 3%						
OUTPUT							
Nominal Power (kVA)	10	15	20	30	40	45	60
Active Power (kW)	9	13,5	18	27	36	40,5	54
Power Factor	0,9						
Nominal Voltage (V)	230V 1-phase / 400V 3-phase +N			400V 3-phase +N			
Voltage variation (static)	+/- 1% (AC-AC / DC-AC)						
Voltage variation (dynamic)	+/- 1% (AC-AC / DC-AC)						
Crest Factor (I _{peak} /I _{rms})	3 : 1						
THDv on nominal power	≤ 0,5% linear load / ≤ 1% not linear load						
Frequency	50 Hz / 60 Hz (autosensing or selectable)						
Frequency stability Battery Mode	0,01%						
Overload capability PF 0.9	125% for 5min, 150% for 30sec with no bypass intervention						
BATTERIES							
Type / UPS Battery Voltage	VRLA - AGM / 240VDC (internal redundant range)						
Runtime / Autonomy	Configurable and extendable, both internally and with additional battery cabinets						
Battery Module	Plug & Play						
GENERAL							
Communication	1 x SNMP Slot, 2 x Serial Port RS232, 1x Logic Level Port, 4 x volt-free contacts ports						
Monitoring	Optional (including 1 x RCCMD License with SNMP Interface Card)						
Display and Signalling	4 x 20-character lines, 4 menu navigation buttons, multi-coloured LED status indicator, alarms and audible signalling						
Diagnostic Functions	Advanced Diagnostic Functions via Display and / or Remote						
Emergency Stop (EPO)	Yes						
Operating Temperature/-Humidity	0°C - 40°C / 20% - 80% non condensing						
Noise level @ 1m (dBA)	42 to 46 dBA						
Protection index	IP 21						
Efficiency Smart Mode	up to 99%						
Net Weight w/o Batteries (kg)	155	155	157	181	184	191	196
Dimensions HxWxD (mm)	1650x414x628			1650x414x1x628			
Certifications	EN 62040-1; EN 62040-2; EN 62040-3 (Voltage Frequency Independent) VFI-SS-111						

For contact information visit www.alphatechnologies.com

The Alpha Group >	North America	Europe, Middle East & Africa		Asia Pacific	Latin & South America
USA Tel: +1 360 647 2360 Fax: +1 360 671 4936	Cyprus Tel: +357 25 375 675 Fax: +357 52 359 595	Germany Tel: +49 9122 79889 0 Fax: +49 9122 79889 21	Lithuania Tel: +370 5 210 5291 Fax: +370 5 210 5292	P.R. China Tel: +852 2736 8663 Fax: +852 2199 7988	Contact USA office
Canada Tel: +1 604 430 1476 Fax: +1 604 430 8908	Russia Tel: +7 495 925 9844 Fax: +7 495 916 1349	United Kingdom Tel: +44 1279 501110 Fax: +44 1279 659870			